



Data sheet DLoG X 10

DLoG antenna
Mechanically stable.
Optimum transmission characteristics.
Reliable, fast data transfer.

Protection class
IP 54 / IP 65 / IP 66 / IP 67
for the entire system.

Mounting
Over 70 mounting solution alternatives.
Stationary and mobile.
Also for non-suspension vehicles.

Thermal concept
Freezer capable.
Robust against fast changing temperatures.

DLoG touch screen
Simple and precise operation.
High breakage resistance.

Mechanical design
Optimal mechanical protection.
Secure against vibrations, impact and environmental conditions.
Tougher testing standards than the US MIL-Std.

Variations

We offer a large selection of design variations and accessories, such as:

4, 10 or 25 front keys



Panel Mount



External keyboard and scanner



DLoG X 10 is a compact, industrial capable Windows® CE terminal. WLAN/GSM connection, a 10" color TFT with touch screen, high IP protection as well as shock and vibration resistance make the DLoG X 10 the ideal terminal for modern logistics and industrial applications.

Used in outside or freezer areas, it bears up in extreme temperatures and is reliable and safe.



Specifications DLoG X 10

Housing		Coated Aluminium Fanless design
Dimensions		8.9" x 11.0" x 3.4" / 226 x 280 x 86 mm (without bracket, without antenna)
Weight		4.0 kg
Display (internal)		Color TFT, 10.4" SVGA, 800 x 600, 230 cd/m ² Color TFT, 10.4" SVGA, 800 x 600, 400 cd/m ²
Touch screen		DLoG specific resistive touch screen
System features		
CPU		Marvell® PXA270 to 520 MHz
Memory		64 MB SDRAM / 64 MB Flash or 128 MB SDRAM / 128 MB Flash
Graphics		Integrated LCD controller
Software		
Operating system		MS® Windows® CE 5.0, CE 6.0 on request
Emulations		VT100, VT220, IBM 5250, TN 3270 Citrix ICA Client® RDP Client
Ports		
Serial		2 RS232 interfaces, alternatively 1 x RS232 and 1 x RS422/485 Optional feature: COM 1, 5 V or 12 V
USB		2 USB 2.0 (low and full speed) interfaces, 1 host and 1 client or 2 host
Keyboard/mouse		Externally via USB port
Slots		
PC Card (16-bit)		1 x type I / type II
CF		1 x type I
Network		
WLAN		WLAN 802.11b/g
Expansion cards		
USB		4 USB ports
Power supply		
AC		110/230 VAC, 100 W, 50 to 60 Hz
DC		24/48 VDC, 60 W and 100 W, galvanically isolated Voltage sags up to 10 VDC can be handled for up to 20 sec. 12 VDC, 100 W, galvanically isolated Voltage sags up to 5 VDC can be handled for up to 20 sec.
Environmental conditions		
Protection class		IP 54 / IP 65 / IP 66 / IP 67
Test marks		CE/FCC Class A
Operating temperature		32 °F to 122 °F / 0 °C to +50 °C -22 °F to 122 °F / -30 °C to +50 °C (with heating only)
Storage temperature		-4 °F to 140 °F / -20 °C to +60 °C
Relative humidity		10 % to 90 % at 104 °F / 40 °C, non-condensing
Vibration / Shock		Class 5M3 according to EN 60721-3-5 Or US Highway Truck as MIL-STD 810F

Highlights

DLoG Config Tool: Diagnostics and individual configuration of the Client

Brightness control: Via integrated front keys

Automatic shut down: Initiated by the ignition signal (automatically) or by the On/Off switch (manually) the operating system is properly shut down and the device is switched off.

Environment controller : Statistics, configuration and monitoring functions (temperature, ignition, backlight, etc.)

Shock and vibration tests to stringent DIN and US Standards: DLoG terminals are suitable for use in locations where heavy vibrations and impacts occur, for example on non-suspension vehicles or machines with substantial imbalances.

Information in this document is subject to change without prior notice. The software and hardware designations used in this text are in most cases also registered trademarks and are thus subject to law.



33 West Higgins Suite 955
South Barrington, IL 60010
Phone: 847 844-3460
Fax: 847 844-3543

info@dlogsfdm.com
www.dlogsfdm.com

DLoG GmbH
Werner-von-Siemens-Str. 13
D-82140 Olching
Phone: +49 81 42 / 28 60-0
Fax: +49 81 42 / 28 60-10
E-Mail: info@dlog.com
Internet: www.dlog.com

© by DLoG GmbH 2008